

NL QuickTouch Keypad

LOCK QT20•N3 Installation

DESCRIPTION

The QT20•N3 QuickTouch Keypad presents a user-friendly design with top reading and effortless code input. Ideal for under-counter equipment or corporate decor and customization.



FEATURES

Battery: Accessible via a drawer at the keypad base

Finish: Black Velvet (ABS)

Enhanced Visibility: Built-in LED lights for use in low-light conditions

MOUNTING INSTRUCTIONS

Cable hole diameter: 3/8" (.953mm) minimum

The hole must be properly deburred to avoid cable damage

The QT20 mounts only on horizontal (9 & 3 o'clock) studs

Affix the two #8-32 (or M4) mounting studs to the safe door

Feed the cable through the spindle hole in the safe door

Align the keypad with the mounting studs

Push down until it snaps into place with a distinct "click"



Pull down the battery drawer at the bottom of the keypad housing

Insert a 9V battery with the positive terminal on the right

Close the battery drawer

Use ONLY Energizer or Duracell ALKALINE batteries.



To remove keypad once installed, push up on keypad housing



*Increase your sales with
Corporate Customization!*



QT20•N3

Works With:

UR20
Universal
RotoBolt

EM20
Large
RotoBolt

EM30
MotorDrive
Lock



QSecurityProducts.com

1014 S. Main Street • Nicholasville, Kentucky 40356 • 859.241.2063

QuickTouch QT20•N3 Installation • Rev. 2501 • ©2025 QSecurity Industries