

# QuickTouch Keypad QT20-N3 Installation



## DESCRIPTION

The QT20-N3 QuickTouch Keypad presents a user-friendly design with top reading and effortless code input. Ideal for under-counter equipment or corporate decor and customization.

## FEATURES

Battery: Accessible via a drawer at the keypad base

Finish: Black Velvet (ABS)

Enhanced Visibility: Built-in LED lights for use in low-light conditions

## MOUNTING INSTRUCTIONS

Cable hole diameter: 3/8" (.953mm) minimum

The hole must be properly deburred to avoid cable damage

The QT20 mounts only on horizontal (9 & 3 o'clock) studs  
Affix the two #8-32 (or M4) mounting studs to the safe door

Feed the cable through the spindle hole in the safe door  
Align the keypad with the mounting studs  
Push down until it snaps into place with a distinct "click"

Pull down the battery drawer at the bottom of the keypad housing  
Insert a 9V battery with the positive terminal on the right  
Close the battery drawer  
Use ONLY Energizer or Duracell ALKALINE or LITHIUM batteries



To remove keypad once installed,  
push up on keypad housing



*Increase your sales with  
Corporate Customization!*

## QT20-N3

**Works With:**

**UR20**  
Universal  
RotoBolt

**EM20**  
Large  
RotoBolt

**EM30**  
MotorDrive  
Lock



QSecurityProducts.com

Nicholasville, Kentucky 40356 • 859.241.2063

QuickTouch QT20-N3 Installation • Rev. 2604 • ©2026 QSecurity Industries